


**2001-009**

## Technical Data Sheet

A low tack protective masking tape for use in interior applications. The product consists of a low density polyethylene film in clear or blue, coated with a custom formulated water based acrylic adhesive.

### Product Characteristics

#### APPLICATIONS

Suitable for the masking and protection of smooth metals such as bright annealed stainless steel, high gloss painted metal, anodized bright aluminum and polished aluminum.

<u>PROPERTIES</u>	<u>US</u>	<u>Metric</u>	<u>Test Method</u>
Nominal Thickness	2.0 ml	50.8 $\mu$	ASTM D882
Nominal Adhesion	0.5 - 3.0 oz/in	5.6 - 33.6 g/cm	PSTC-1
Tensile	MD 2900 psi	203 kg/cm <sup>2</sup>	ASTM D882
	TD 2200 psi	154 kg/cm <sup>2</sup>	ASTM D882
Elongation	MD 400%	.....	ASTM D882
	TD 500%	.....	ASTM D882

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape representative.