

TECHNICAL DATA SHEET

3001-006R

PRODUCT DESCRIPTION

A very low tack protective masking tape for use in interior applications. The product consists of a low density polyethylene self-wound film, coated with a custom formulated water based acrylic adhesive.

APPLICATIONS

Ideal for the masking and protection of very smooth, glossy surfaces such as LCD, float and architectural coated and reflective glass and polycarbonate, polyester, acrylic sheeting.

<u>PROPERTIES</u>		<u>US</u>	<u>Metric</u>	<u>Test Method</u>
Nominal Thickness		3.0 ml	76.2 μ	ASTM D3652
Adhesion Range		0.5 – 1.5 oz/in	5.6 – 16.8 g/cm	PSTC-1
Tensile	MD	3500 psi	245 kg/cm ²	ASTM D882
	TD	2900 psi	203 kg/cm ²	ASTM D882
Elongation	MD	450%	ASTM D882
	TD	750%	ASTM D882

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape Representative. 12/12