

## TECHNICAL DATA SHEET

# 3001-009

### PRODUCT DESCRIPTION

A low tack masking tape for use in interior applications. The product consists of a low density polyethylene film in clear or blue, coated with a custom formulated water based acrylic adhesive.

### APPLICATIONS

Suitable for the masking and protection of smooth metals such as bright annealed stainless steel, high gloss painted metal, anodized bright aluminum and polished aluminum.

PROPERTIES		US	Metric	Test Method
Nominal Thickness		3.0 ml	76.2 $\mu$	ASTM D3652
Adhesion Range		0.5 – 3.0 oz/in	5.6 – 33.6 g/cm	PSTC-1
Tensile	MD	3200 psi	224 kg/cm <sup>2</sup>	ASTM D882
	TD	2500 psi	175 kg/cm <sup>2</sup>	ASTM D882
Elongation	MD	450%	.....	ASTM D882
	TD	750%	.....	ASTM D882

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Main Tape assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Main Tape product proven defective. For full disclosure of the Limited Warranty, please contact your Main Tape Representative. 11/12